

Appendix 2: Clean version of Specifications-Ser.No.10/601,240**Floss Dispenser With Dynamic Tension Control****Field of the Invention**

The present invention relates to a dental floss dispenser, and more particular to a floss
5 dispenser integrating advantages of conventional toothpick as well as floss box. The floss
dispenser includes a bracket on which the floss is robustly supported for facilitating easy
and smooth cleaning process between the teeth. In addition, the floss can be replaced
anytime according to the necessity. The floss dispenser features simple configuration
while the length of floss for flossing can be economically used.

10

Description of the Prior Art

Conventionally, dental floss is used to remove food debris and dental plaque between
teeth by flossing plaque out of the space between two teeth, extending the floss to gingival
sulcus, and then sweeping along teeth surface thereby preventing any bacteria growing
15 there. There are many commercial available floss in the form of floss box and toothpick
for the dental cleaning purpose.

In use, a certain length of floss is cut from the floss box, and tensioned between
fingers from both hands. Then the floss cuts into the space between two adjacent teeth,
and with the upward and downward movement of the floss therealong, the food debris can
20 be kicking off therefrom.

However, this conventional application has the following disadvantages. Firstly,
hands carry bacteria and bring into the mouth during the cleaning process. Secondly, the
length of the floss is hard to control. If it is too short, then it imposes a difficulty in
cleaning, if it is too long, then it is surely a waste. Even there are toothpicks bonded with
25 floss holder, this disposable toothpick is really not healthy to our environment from a
pollution viewpoint.

Appendix 2: Clean version of Specifications-Ser.No.10/601,240**Summary of the Invention**

It is an object of this invention to provide a floss dispenser in which the length of the floss can be accurately controlled, while the tension of the floss is also properly controlled
5 so as to provide a user-friendly application.

In order to achieve the object set forth, provided is a floss dispenser in accordance with the present invention comprises a housing defining at least a receiving chamber with a floss bobbin rotationally received therein. A floss fork is arranged at an end of the housing for bracing a section of floss thereon. A first tension-controlling device is
10 arranged on the housing controlling a tension of the floss after the floss fork. And a tensioner is arranged adjacent to the feeding device controlling the tension between the floss bobbin and the floss fork.

By the provision of the tensioner, the tension of the floss can be properly and dynamically controlled during the flossing process, and the tension of the floss can be
15 released after the flossing process.

Brief Description of the Drawings

Figure 1 is an exploded perspective view of a floss dispenser in accordance with the present invention;

20 Figure 2 is an assembled view of Figure 1;

Figure 3 is an illustration showing a floss extending through an eyelet of a circular slot;

Figure 3A is an enlarged view circled in Figure 3;

Figure 4 is an illustration showing the floss route through a first section of floss
25 dispenser;

Figure 4A shows the floss completes its route on the first section;

Appendix 2: Clean version of Specifications-Ser.No.10/601,240

Figure 5 shows the floss routes through a tension controller;

Figure 5A shows details thereof;

Figure 5B is an enlarged view thereof;

Figure 6 shows the floss routes through a thread hole of a tensioner;

5 Figure 7 is an illustration showing the floss is well supported on a bracket of the floss dispenser;

Figure 7A is a top view thereof;

Figure 8 is an illustration showing the movement of the tensioner of the floss dispenser;

10 Figure 8A shows the floss is locked by the tensioner;

Figure 9 shows the floss is released by the tensioner for replacing new floss;

Figure 9A shows a top view of Figure 9 and

Figure 10 shows used floss is cut off by a cutter.

15 **Detailed Description of Preferred Embodiment**

Referring to Figure 1, an exploded view of a floss dispenser according to the present invention is shown. The floss dispenser generally includes a housing 1 on which a detachable cover 2 is attached. The floss dispenser further includes a floss bobbin 3, a ratchet 4 and stopper 5, a tensioner 6 and a cutter 7.

20 The housing 1 defines a receiving chamber 11 in which a bobbin shaft 12 is mounted. The receiving chamber 11 further defines a feeding hole 1A and a side feeding hole 1B (see Figures 4 and 4A). The housing 1 further includes a cutter cell 13 adjacent to the receiving chamber 11 in a middle portion thereof. A cutting knife 7 is assembled into the cutter cell 13 by means of a screw 72 through a hole 71 of the cutting knife 7. The
25 housing 1 further includes a ratchet socket 14 in which the ratchet 4 is installed. The ratchet 4 is moveably assembled in the ratchet socket 14 by a screw 43 and other

Appendix 2: Clean version of Specifications-Ser.No.10/601,240

assembling kits which will be described in detail later. Adjacent to the ratchet socket 14, a stopper cell 16 in communication with the ratchet socket 14 is provided. The stopper 5 is mounted in the stopper cell 16 by means of a screw 52 through a mount 51 thereof. The stopper 5 extends into teeth of the ratchet 4 such that the ratchet 4 can rotate along
5 clockwise.

Adjacent to the ratchet socket 14, a tensioner bracket 17 is provided. The tensioner bracket 17 defines a feeding hole 1C and a shaft hole 17A for assembling the tensioner 6 therein. The tensioner 6 is mounted into the tensioner bracket 17 by means of a rivet 63. Finally, at the opposite end of the receiving chamber 11, a floss fork 10 is provided. The
10 floss fork 10 defines a guiding slot 10A along its outer surface, and a pair of notches 10B at ends of the fork for supporting the floss therebetween. A post 10C is provided adjacent to an inner beam of the fork 10.

Referring to Figure 2, after the floss bobbin 3 is disposed within the receiving chamber 11, the cover 2 is attached so as to enclose the bobbin 3 therein. A detachable threaded
15 (not shown) is selectively provided for inserting into the feeding hole 1A. The threader includes a passage through which the floss extends.

As mentioned above, the ratchet 4 is assembled into the ratchet socket 14 by means of the assembling kit which is configured by a slotted shaft 41 and a shaft 42. A rubber member (not shown) is selectively arranged within slots of the slotted shaft 41. By this
20 arrangement, the ratchet 4 can be assembled into a supporting hole 15 of the ratchet socket 14 by means of the screw 43.

Referring now to Figures 3, 4 and 5, a floss route along the dispenser is shown in detail. After the floss bobbin 3 is rotationally assembled into the receiving chamber 11, the floss is firstly extended through the passage of the threader. Then the floss passes
25 further through the side feeding hole 1B, the feeding hole 1C of the tensioner bracket 17 and is thereafter further extended through a passage 62 of the tensioner 6.

Appendix 2: Clean version of Specifications-Ser.No.10/601,240

Firstly, a threading device 8 is used to move the floss 3A through the passage of the threader. Then the floss 3A is routed through the feeding hole 1A and comes out therefrom to one side of the housing 1. The floss 3A is further threaded through the side feeding hole 1B and the feeding hole 1C of the tensioner bracket 17, as shown in Figures 4A and 4. Then the tensioner 6 is slightly moved such that the floss 3A can pass through the passage 62 of the tensioner 6. By this arrangement, the tensioner 6 applies a certain tension to the floss 3A.

Then, the floss 3A routes through the guiding slot 10A of the floss fork 10, as shown in Figures 7 and 7A. The floss 3A then routes along the notches 10B of the fork, and is finally anchored at the post 10C. The floss 3A further routes to the slotted shaft 41 of the ratchet 4 and extends through the slots 41A of the slotted shaft 41 to be held thereby. Preferably, the slotted shaft 41 is inserted with a rubber, which imposes a friction to the floss 3A, the floss 3A can then be securely held. As a result, the floss 3A completes its routing and holds with proper tension.

When the floss 3A completes its routes and a user would like to use it to floss, the user may slightly press on the tensioner 6 such that the floss 3A is tensioned. Then the user may rotate the ratchet 4 so as to further tension the floss 3A by the arrangement between the ratchet 4 and the stopper 5. Finally, the user can use the floss 3A spanning between the floss fork 10 for flossing. Specially, the tension of the floss 3C can be adjusted anytime by the ratchet 4.

After a section of floss 3A is used, the used floss 3A can be easily replaced, as shown in Figures 9 and 9A. The floss 3A braced between the fork 10 can be easily released from the notches 10B by a further push back of the tensioner 6 so as to release the tension applied to the floss 3A. As a result, the floss 3A can be easily released from the notches 10B. Then the used floss 3A can be cut off by the knife 7, as shown in Figure 10. A new section of floss 3A can be re-routed to the fork 10 according to the procedures

Appendix 2: Clean version of Specifications-Ser.No.10/601,240

described above. After the floss bobbin 3 is exhausted, a new floss bobbin 3 can be refilled and the user may start a cycle of flossing.

The floss dispenser made according to the present invention can be featured with at least the following advantages.

5 1. The floss dispenser made in accordance with the present invention features the advantages from both the floss box and the toothpick with floss holder. The user can easily use it to floss. In addition, the floss can be easily replaced while the floss can be economically controlled.

10 2. The floss dispenser made in accordance with the present invention further features a simplified configuration readily for handling. By the provision of the ratchet and tensioner, the tension of the floss can be accurately controlled thereby preventing the break of the floss during the flossing.

From the above description, it can be easily appreciated that the tension of the floss is controlled by both the ratchet after the floss routes through the post, and by the tensioner
15 right before the floss reach the floss fork. This two stage controlling of the floss, especially the tensioner, provides a dynamic control of the tension of the floss. As such, the user may easily perform the flossing process.

It should be note that the specification relating to the above embodiment should be construed as exemplary rather than as limitation of the present invention, with many
20 variations and modifications being readily attainable by a person of skill in the art without departing from the spirit or scope thereof as defined by the appended claims and their legal equivalents.

Appendix 2: Clean version of Specifications-Ser.No.10/601,240**I Claim:**

1. (Currently Amended) A floss dispenser, comprising:
a housing defining at least a receiving chamber with a floss bobbin rotationally received therein;
5 a floss fork arranged at an end of the housing for bracing a section of floss thereon;
a first tension controlling device arranged on the housing for controlling tension of the floss from the floss bobbin; and
a tensioner movably mounted to the housing and defining a passage through which the floss extends to selectively apply tension to the floss by the movement of the tensioner.
10
2. (Currently Amended) A floss dispenser as recited in claim 1, further comprising a cover removably attached to the housing to enclose the receiving chamber.
3. (Original) The floss dispenser as recited in claim 2, wherein the receiving chamber
15 includes a feeding hole in which a threader having a passage is mounted.
4. (Currently Amended) The floss dispenser as recited in claim 1, wherein the first tension controlling device is a ratchet having a slotted shaft through which a portion of the floss extends for securely anchoring the floss.
20
5. (Currently Amended) The floss dispenser as recited in claim 4, wherein the ratchet is provided with a stopper such that the ratchet runs only in a single direction.
6. (Currently Amended) The floss dispenser as recited in claim 1, wherein the tensioner
25 is mounted to the housing by a tensioner bracket of the housing.

Appendix 2: Clean version of Specifications-Ser.No.10/601,240

7. (Original) The floss dispenser as recited in claim 1, wherein the housing provides a cutter so as to cut the floss to a suitable length.
8. (Original) The floss dispenser as recited in claim 1, wherein the floss fork includes a post for anchoring of the floss.
9. (Currently Amended) The floss dispenser as recited in claim 1, wherein the tensioner is movable in a direction to release the tension of the floss so as to allow the floss to be removed from the floss fork thereby releasing the floss therefrom.
10. (Original) The floss dispenser as recited in claim 1, further comprising a threader for easily threading the floss through feeding holes and passages of the housing.
11. (Original) The floss dispenser as recited in claim 1, wherein the floss routes from the receiving chamber, further through a passage of the tensioner, a guiding slot of the floss fork, then braced by notches defined in ends of the fork, anchoring around a post adjacent to the floss fork, and finally securely anchored the feeding device.
12. (Currently Amended) A floss dispenser, comprising:
- a housing defining at least a receiving chamber with a floss bobbin rotationally received therein;
 - a floss fork arranged at an end of the housing for bracing a section of floss thereon;
 - a first tension controlling device arranged on the housing for controlling tension of the floss after the floss fork; and
 - a tensioner movably mounted to the housing and defining a passage through which the floss extends for dynamically controlling tension between the floss bobbin and the floss

Appendix 2: Clean version of Specifications-Ser.No.10/601,240

fork during a flossing process.

13. (Currently Amended) The floss dispenser as recited in claim 12, wherein the tensioner is moveable to selectively apply the tension to the floss or to release the tension therefrom.

5

14. (Original) The floss dispenser as recited in claim 12, wherein the floss fork defines a guiding slot for properly guiding the floss.

Appendix 2: Clean version of Specifications-Ser.No.10/601,240**Floss Dispenser With Dynamic Tension Control****Abstract of the Invention**

- Provided is a floss dispenser comprises a housing defining at least a receiving chamber
- 5 with a floss bobbin rotationally received therein. A floss fork is arranged at an end of the housing for bracing a section of floss thereon. A first tension-controlling device is arranged on the housing controlling a tension of the floss after the floss fork. And a tensioner is arranged adjacent to the feeding device controlling the tension between the floss bobbin and the floss fork.
- 10 By the provision of the tensioner, the tension of the floss can be properly controlled during the flossing process, and the tension of the floss can be released after the flossing process.